

Data sheet – Fire Hydrants

Angle Valves

90° 法蘭消火栓
Flanged Fire Hydrant

Standard: BS5154: 1991
标准: BS5154: 1991

Water inlet 進水規格	Water outlet 出水規格	D (mm)	H (mm)	Material 材料
40mm 1½"	40mm 1½" BSP	145	193	Brass 黃銅 Bronze 青銅 (LG2)
50mm 2"	50mm 2" BSP	165	205	
65mm 2½"	65mm 2½" BSP	185	225	




注：可选配接中国式、德式、英式、町野式等各种接头使用。

Globe Valves

180° 法蘭消火栓
Flanged Fire Hydrant

Standard: BS5154: 1991
标准: BS5154: 1991

Water inlet 進水規格	Water outlet 出水規格	D (mm)	H (mm)	L (mm)	Material 材料
40mm 1½"	40mm 1½" BSP	145	136	150	Brass 黃銅 Bronze 青銅 (LG2)
50mm 2"	50mm 2" BSP	165	160	160	
65mm 2½"	65mm 2½" BSP	185	165	185	



注：可选配接中国式、德式、英式、町野式等各种接头使用。

Note: The flange diameter & holes are different for hydrant valves with JIS standard flanges or ANSI standard flanges.

Contact us if you need more information.

Outlet: normally with BSP male threads, can be fitted with different adaptors upon request.

Kunshan EMF Industrial Co., Ltd.